



Model No.		TCA3TDHVACHGRH2401P		
Nominal cooling capacity	KW	11.3		
	RT	3.2		
Power Input	KW	3.9		
EER (Btu/W.h)	/	10.1		
Power Supply	/	1/N/PE AC240V±10% 60HZ		
Refrigerant Gas	/	R32		
Rated Cooling Running Current	A	16		
Min. Start Current	A	21		
Connection	Suction	in	5/8	
	Liquid Reheat	in	1/2	
	Liquid	in	3/8	
Outdoor Condenser Unit	Condenser Type	/	Air Cooled Copper Pipes & Aluminum Fins Type Heat Exchanger	
	Compressor Type	/	Hermetic Scroll Type	
	Compressor Quantity	PCS	1	
	Fan Type and Quantity	PCS	Axial fans/1	
	Fan Flow Rate	CFM	4750	
	Length-A	in	30	
	Width-B	in	30	
	Height-C	in	43	
	Weight	lbs	194	
Noise	dB(A)	≤60		





Cultivated Solutions For Optimal Growth

400 N St. Paul Dallas, Tx 75201 sales@tricleanair.com

Ph: (972) 656-9032 - WWW.TRICLEANAIR.COM

Model No.		TCA3TDHVACHGRHAHU2401P	
Nominal cooling capacity	KW	11.3	
	RT	3.2	
Power Input	KW	0.8	
P/kWH	/	21.3	
Power Supply	/	1/N/PE AC240V±10% 60HZ	
Refrigerant Gas	/	R32	
Rated Cooling Running Current	A	3.3	
Min. Start Current	A	5	
Connection	Suction	in	5/8
	Liquid Reheat	in	1/2
	Liquid	in	3/8
Indoor Evaporator Unit	Direct Expansion Cooling Coil	/	Copper Pipes & Aluminum Fins Type Heat Exchanger for Refrigerant Gas
	Direct Expansion Re-Heat Coil	Type	Copper Pipes & Aluminum Fins Type Heat Exchanger for Hot Gas ReHeat
		BTU	27,000
	Fan Type and Quantity	PCS	Centrifugal fans/ @ 450 watts each
	Fan Flow Rate	CFM	2500
	External Static Pressure	Pa	300
	Drain Pipe	in	1
	Length-L	in	32
	Width-W	in	45
	Height-H	in	28
Weight	lbs	220	
Noise	dB(A)	≤60	



Cultivated Solutions For Optimal Growth

400 N St. Paul Dallas, Tx 75201 sales@tricleanair.com