



Model No.		TCA5TDHVACHGRH2401P	
Nominal cooling capacity	KW	20.7	
	RT	5.9	
Power Input	KW	6.5	
EER (Btu/W.h)	/	10.9	
Power Supply	/	1/N/PE AC240V±10% 60HZ	
Refrigerant Gas	/	R32	
Rated Cooling Running Current	A	33	
Min. Start Current	A	41	
Connection	Suction	in	3/4
	Liquid Reheat	in	1/2
	Liquid	in	1/2
Outdoor Condenser Unit	Condenser Type	/	Air Cooled Copper Pipes & Aluminum Fins Type Heat Exchanger
	Compressor Type	/	Hermetic Scroll Type
	Compressor Quantity	PCS	1
	Fan Type and Quantity	PCS	Axial fans/1
	Fan Flow Rate	CFM	4750
	Length-A	in	30
	Width-B	in	30
	Height-C	in	43
	Weight	lbs	227
Noise	dB(A)	≤63	





Cultivated Solutions For Optimal Growth

400 N St. Paul Dallas, Tx 75201 sales@tricleanair.com

Ph: (972) 656-9032 - WWW.TRICLEANAIR.COM

Model No.		TCA5TDHVACHGRHAHU2401P	
Nominal cooling capacity	KW	20.7	
	RT	5.9	
Power Input	KW	0.9	
P/kWH	/	34.9	
Power Supply	/	1/N/PE AC240V±10% 60HZ	
Refrigerant Gas	/	R32	
Rated Cooling Running Current	A	3.8	
Min. Start Current	A	5	
Connection	Suction	in	3/4
	Liquid Reheat	in	1/2
	Liquid	in	1/2
Indoor Evaporator Unit	Direct Expansion Cooling Coil	/	Copper Pipes & Aluminum Fins Type Heat Exchanger for Refrigerant Gas
	Direct Expansion Re-Heat Coil	Type	Copper Pipes & Aluminum Fins Type Heat Exchanger for Hot Gas ReHeat
		BTU	53,000
	Fan Type and Quantity	PCS	Centrifugal fans/ @ 550 watts each
	Fan Flow Rate	CFM	3,000
	External Static Pressure	Pa	300
	Drain Pipe	in	1
	Length-L	in	32
	Width-W	in	45
	Height-H	in	28
Weight	lbs	231	
Noise	dB(A)	≤63	



Cultivated Solutions For Optimal Growth

400 N St. Paul Dallas, Tx 75201 sales@tricleanair.com



Ph: (972) 656-9032 - WWW.TRICLEANAIR.COM